

Thermofluid Dynamics in Molten Reactor Core Pool
Surrounded by Crust at High Pressure

J. I. Yun,

Future & Challenge Tech. Co.

San 56-1 Sillim-Dong, Kwanak-Gu, Seoul, 151-742, Korea

K. Y. Suh, C. S. Kang

Department of Nuclear Engineering, Seoul National University

San 56-1 Sillim-Dong, Kwanak-Gu, Seoul, 151-742, Korea

Abstract

Heat transfer and fluid flow in a molten pool are influenced by internal volumetric heat generated from the radioactive decay of fission product species retained in the pool. The pool superheat is determined based on the overall energy balance that equates the heat production rate to the heat loss rate. Decay heat of fission products in the pool was estimated by product of the mass concentration and energy conversion factor of each fission product. For the calculation of heat generation rate in the pool, twenty-nine elements were chosen and classified by their chemical properties. The mass concentration of a fission product is obtained from released fraction and the tabular output of the ORIGEN 2 code. The initial core and pool inventories at each time can also be estimated using ORIGEN 2. The released fraction of each fission product is calculated based on the bubble dynamics and mass transport. Numerical analysis was performed for the TMI-2 accident. The pool is assumed to be a partially filled hemispherical geometry and the change of pool geometry during the numerical calculation was neglected. From the results of numerical calculation, peak temperature of molten pool significantly decreased and volatile fission product was almost released from the molten pool during the accidents.