

Analysis on Chemical Ingredients with Anti-microbial Activity in Water-based Metalworking Fluids

Donguk Park[†], Bok Hwan Kim[†], Kwonsup Lee^{*}

[†] *Department of Environmental Health, Korea National Open University, Dongsung-dong,
Jongro-ku, Seoul, South Korea, 110-791*

^{*} *Occupational Safety and Health Research Institute, Korea Occupational Safety and Health Agency,
34-3, Gusan-dong, Bupyung-gu, Incheon, 403-711*

Abstract : This study was conducted to estimate if the level of several chemical ingredients including alkanolamines or ethanolamines (EA) examined in the specific synthetic metalworking fluid (MWF) "A" can cause anti-microbial activity and health effect. Three water-based MWF products ("A", "B", and "C") were studied every week for two months. Chemical ingredients such as formaldehyde, boron, EA, and copper were examined. In the sump where MWF "A" was used, not only the total level of EA, monoethanolamine(MEA), diethanolamine(DEA) and triethanolamine(TEA), but also boron level were significantly higher than those of the other MWFs. ANOVA statistical tests indicated that levels of pH, alkalinity, boron, MEA, DEA and TEA in MWF "A" were significantly higher than those in other MWF types. Correlation tests also found that levels of pH, alkalinity, boron, MEA, DEA and TEA in MWF "A" are significantly correlated. We suggested the assumptions that excessive concentrations of EA, and borate at a high pH level, may cause anti-microbial resistance synergically. To demonstrate this assumption, additional study is needed to examine the relationship between the levels of microbes and excessive concentrations of EA, and borate at a high pH level.

Keywords : synthetic metalworking fluids, monoethanolamine (MEA), diethanolamine (DEA), triethanolamine (MEA).

Introduction

Limited information exists about the chemical components of specific MWFs because of the highly competitive and proprietary nature of the metalworking industry [1].

Water-based MWFs are excellent nutritional sources for many kinds of bacteria and fungi.

A specific synthetic MWF (designated as MWF "A"), imported from Japan, was acclaimed to have excellent anti-microbial activity. The owner of this machine shop determined that risk of MWF "A" needs to be assessed before it is introduced to other sumps. We were asked to evaluate whether the use of this fluid is appropriate for both worker health and operation. The Material Safety Data

Sheets (MSDS) on MWF “A” indicated only a presence of carboxylic salts, synthetic oil, and EA. The specific amount and type of EA were not addressed due to confidential trade secrets. The MSDS was not a useful reference for the presence, or relative amount of components. Alkanolamines or ethanolamines (EA) such as monoethanolamine (MEA), diethanolamine (DEA) and triethanolamine (TEA) may be used in soluble MWFs in order to stabilize pH or inhibit corrosion. This study was conducted to examine if their levels in a specific synthetic metalworking fluid (MWF) “A” can cause anti-microbial activity and health effect. To accomplish this purpose, several chemical ingredients that were suspected to have anti-microbial performance were investigated and compared among MWFs.

Methods

MWF type and sump studied

Three types of water-based MWFs (MWF “A”, “B” and “C”) were studied every week for two months (from June 1, 2002 to July 30, 2002) in a single machine shop. MWF “A”, a synthetic type, was first charged to one sump called MT 01 on September 1, 2001. This MWF had been used without replacement until July 30, 2002, the end of this study. Two other products of soluble MWFs (“B” and “C”) were used in six other sumps, for both longer and shorter periods than the synthetic MWF “A”, again without changing the fluid.

MWF sump bulk sample collection and measurement

The pH levels of the MWFs were measured in the field using a thermometer (model 230, Portable Meter, ORION). In addition, the MWF concentration was measured in the field using a refractometer (model, ATAGO N20E, Japan). Total alkalinity was analyzed in laboratory according to “method No. 2320 A” of the “Standard Methods for Examination of Water and Wastewater”[3]. Copper and Boron compounds in the MWFs were quantified as elements using Inductively Coupled Plasma (model OPTIMA 3,000 DV, Perkin Elma). A portion of MWF sample was filtered using a micro-syringe, with a 0.4 µm pore size filter, and quantified by ion chromatography (WATERS, Waters, USA) equipped with composed of a guard column (IC PAK™ C M/D, USA), column (IC PAK™ Cation M/D column, USA), and a detector (432 conductivity detector, Waters, USA). Statistical testing was carried out using SPSS standard version. Correlation tests among pH, MWFs concentration and chemical ingredients in MWFs were computed. ANOVA test was performed to compare the differences of chemical ingredients levels among MWF types.

Results

The study results on pH level, MWF concentration, alkalinity and chemical components by MWF types are indicated in Table 1. The pH level of the MWF “A” ranged from 9.01 to 9.38 (average: 9.14) and was significantly higher level than those in other sumps. Total alkalinity ranged from 15,200 ppm to 14,700 ppm, which was far higher than the range of other sumps, 1,300 ppm – 5,200

ppm. Correlation tests indicated EA levels are significantly correlated with alkalinity concentration. The levels of alkalinity, boron and EA are compared in Fig. 1. Elemental concentrations of boron in the MWF "A" were also significantly higher than those in other MWFs. The average of total EA in MWF "A" (range: 35,595 ppm to 57,857 ppm). This level was over ten times higher than the averages in MWF "B" and "C". Furthermore, concentrations of MEA, DEA and TEA were also significantly higher than those in other sumps. In particular, TEA accounted for 84 % of the total EA. Total level of EA ranged from 35,595 ppm to 57,857 ppm. ANOVA statistical tests showed that levels of pH, alkalinity, boron, MEA, DEA and TEA in MWF "A" were significantly higher than those in other MWF types (Table 1 and Fig. 1). Correlation tests also found that correlation among levels of pH, alkalinity, boron, MEA, DEA and TEA in MWF are significant.

Discussion

Chemical additives such as biocide are added in water-based MWFs to prevent excessive microbial growth. In particular, information on amount and components of chemical ingredients contained in MWF were not fully addressed on MSDS. Our results of pH level and MWF temperature indicated that all MWFs provided appropriate environmental conditions for microbial growth. Although the synthetic MWF "A" had been used without replacement for 12 months, fluid contamination from microorganisms had not been found.

As was indicated Table 1 and Fig. 1, the levels of EA, alkalinity and boron between MWF "A" and the other MWFs ("B" and "C") were significantly different. In particular, high level of EA and alkalinity were found in MWFs "A". Excessive amount of EA may result in high level of alkalinity. It could be suggested that abuse of EA and boron could contribute to strong anti-microbial performance in MWFs. The levels of EA we investigated were far higher than those reported on MSDS. Boron was not addressed on MSDS. This results demonstrated that MSDS was not useful for worker's right to know toxicity of ingredients in MWF "A". There have been several studies stating that TEA, DEA, and MEA inhibit the growth of a wide variety of microorganisms [4-9]. Our study found significant difference in pH, boron, MEA, DEA and TEA between MWF "A" and the other two MWF (Table 1). Statistical tests indicated that the levels of pH, boron, MEA, DEA and TEA were significantly correlated. These study results suggest the assumption that a high EA level in combination with borate at a high pH (9.01-9.38) can lead to anti-microbial resistance in MWF "A".

Although EA might improve anti-microbial performance, it is certain that excessive amounts of EA can cause adverse health effects. EA has been associated with respiratory irritant and a sensitization [2]. Manufacturer has to design MWFs that can be both microbiologically resistant in use, as well as nontoxic. It is not easy work to develop MWF satisfied with these dual goals. Water-based MWF that may include base oils (synthetic, semi-synthetic, petroleum oil), water, emulsifiers, preservatives and other additives, eventually undergo microbial degradation. However, it is technically impossible for end users to evaluate a manufacturer's claims that their fluids are resistant and therefore, do not require biocide additions. Our study also addresses a really important

issue in the failure to report ingredients on the MSDS.

Conclusions

Our study found that levels of pH, alkalinity, boron, MEA, DEA and TEA in MWF "A" were significantly higher than those in other MWF types and correlated. Abuse of EA and boron could contribute to strong anti-microbial performance in MWFs. These study results suggest the assumption that a high EA level in combination with borate at a high pH (9.01-9.38) can lead to anti-microbial resistance in MWF "A". Future research is needed to examine whether excessive concentration of EA, and borate at a high pH level may cause anti-microbial activity. For this study level of microbes that can be regarded as contamination indicator should be analyzed.

References

1. National Institute for Occupational Safety and Health (NIOSH). "Criteria for a recommended standard: Occupational exposure to metalworking fluids." U.S. Department of Health and Human Services, Public Health Service, Centers for Disease Control and Prevention, Cincinnati, Ohio: National Institute for Occupational Safety and Health, 1998.
2. Savonius B. H., Kanerva L., "Occupational asthma caused by ethanolamines," *Allergy*, Vol. 49, No. 10, pp. 877-881, 1994.
3. American Public Health Association (APHA), American Water Works Association (AWWA), Water Environmental Federation (WEF). "Standard methods for examination of water and wastewater", 19th Ed., # 2320 A, APHA, pp. 2-25, 1995.
4. Beyer K. H., Smith J., Jones R., "Final report on the safety assessment of triethanolamine, diethanolamine, and monoethanolamine," *J. Ame. Coll. Tox.*, Vol. 2, No. 7, pp. 183-235, 1983.
5. Hernandez P. M., Larsen I. C., Petersen C. R., "The various factors involved in developing a microbial-resistant aqueous cutting fluid," *Lub. Eng.*, Vol. 41, pp. 425-429, 1984.
6. Sandin M., Allenmark S., Edebo L., "Selective toxicity of alkanolamines," *Antimicrobial Agents and Chemotherapy*, Vol. 34, No. 3, pp. 491-493, 1990.
7. Steiner B., Omelkova J., Proks B., Sasinkova V., Koos M., "Aliphatic 1,2-Alkanolamines-inhibitors of β -glucanase from *Candida utilis* Fols," *Microbiology*, Vol. 38, No. 5, pp. 392-394, 1993.
8. Bennett E. O., "Corrosion inhibitors as preservatives for metalworking fluids-ethanolamines," *Lub. Eng.*, Vol. 35, pp. 137-144, 1979.
9. Rossmore W. R., "Biostatic fluids, friendly bacteria, and other MYTHS in metalworking microbiology," *Lub. Eng.*, pp. 253-260, 1993.

Table 1. Summary of levels in bulk sump samples of water-based metalworking fluids (MWF “A” used in sump MT 01, MWF “B” in two sumps, and MWF “C” in four sumps)

	MWF “A”		MWF “B”		MWF “C”		ANOVA	
	Sample No	Average (SD)	Sample No	Average (SD)	Sample No	Average (SD)	F-ratio	p-value
MWF pH	8	9.14 (0.12)	16	8.64 (0.50)	32	8.92 (0.42)	4.25	0.019
MWF Temperature (°C)	8	22.6 (3.6)	8	24.0 (3.18)	32	23.4 (3.09)	0.261	0.773
MWF concentration (%)	8	6.2 (0.65)	16	5.4 (1.49)	32	7.0 (2.56)	3.003	0.055
Alkalinity, mg/l	8	13,838 (941)	16	2,869 (695)	32	3,497 (964)	480.9	0.000
Boron, mg/l	8	105.1 (13.9)	13(3) ¹	12.7 (8.9)	28(4) ¹	14.4 (13.9)	171.3	0.000
Copper, mg/l	1 (7) ¹	0.2	16	12.4 (6.9)	30(2) ¹	25.9 (17.6)	5.265	0.009
Formaldehyde, mg/l	8	285 (58)	32	311 (150)	32	95 (112)	0.451	0.991
MEA, ppm	8	4,036 (687)	5 (11) ¹	680 (437)	20(12) ¹	1,296 (614)	73.86	0.000
DEA, ppm	8	2,386 (384)	0 (16) ¹	not detected	2(30) ¹	971 (583)	7.053	0.017
MEA, ppm	8	34,480 (6,537)	15 (1) ¹	520 (377)	32	1,229 (651)	680.2	0.000
Total ethanolamine, ppm	8	40,903 (6,888)	15 (1) ¹	622 (714)	32	2,003 (1,378)	742.8	0.000

Sample number: Number of sumps where each type of MWF was used x 8 measurements

¹ : Sample number in parenthesis = number of sample not detected, average and standard deviation were from results of samples detected.

MEA Monoethanolamine, DEA Diethanolamine, TEA Triethanolamine

Table 2. Correlation matrix among chemical ingredients in MWFs

	MWF conc	pH	Boron	Copper	Alkalinity	MEA	DEA	TEA
MWF conc	1	0.38	-0.21	0.83**	0.06	0.28	-0.06	-0.03
pH	0.38	1	0.53	0.03	0.51	0.73**	0.51	0.52
Boron	-0.21	0.53	1	-0.64	0.94***	0.84**	0.97***	0.97***
Copper	0.83	0.03	-0.64	1	-0.41	-0.16	-0.47	-0.47
Alkalinity	0.06	0.51	0.94	-0.41	1	0.93***	0.99***	0.99***
MEA	0.28	0.73	0.84	-0.16	0.93	1	0.91***	0.92***
DEA	-0.06	0.51	0.97	-0.47	0.99	0.91	1	0.99***
TEA	-0.03	0.52	0.97	-0.47	0.99	0.92	0.99	1

*** p<0.01

** 0.01<p<0.05

MEA Monoethanolamine, DEA Diethanolamine, TEA Triethanolamine

Fig. 1. Comparison of boron, alkalinity and Eas by MWF type and sump (MT01 ; MWF "A", NC01 & NC02 ; MWF "B", MT02, ML04, ML06 & DM10; MWF "C").

MEA: Monoethanolamine, DEA Diethanolamine, TEA Triethanolamine

