

Effects of Precursor Composition on the J_c of YBCO Thin Films Prepared by DCA-MOD Method

Byeong-Joo Kim, Hye-Jin Kim, Jong-Beum Lee, Hee-Gyoun Lee and Gye-Won Hong*

Department of Advanced Materials Engineering, Korea Polytechnic University, Korea

YBa₂Cu₃O_{7- δ} films have been prepared on LaAlO₃ (100) single-crystal substrates by the metal organic deposition using dichloroacetate precursors (DCA-MOD). Yttrium-excess (15 at%), barium-poor (0.5 at%), and a stoichiometric(Y:Ba:Cu=1:2:3) DCA precursor solutions were prepared in order to investigate the effects of precursor composition in YBCO films prepared by DCA-MOD method. Coated films were calcined at low temperature up to 500°C in flowing humid oxygen atmosphere. Conversion heat treatment was performed 800°C for 2 h in flowing Ar gas containing 1000 ppm oxygen with a humidity of 9.45%. For the film prepared using excess yttrium composition, high critical current density (J_c) of >2MA/cm² was obtained whereas, for the films prepared using barium-poor composition, J_c was lower than 1MA/cm².

keywords : thin film, YBCO, DCA-MOD, Yttrium-excess, barium-poor

Acknowledgement:

This study was partly supported by the grant from Energy and Electric Power Education Center program and funded by Ministry of Commerce, Industry and Energy(MOCIE), Republic of Korea.