

University of Tehran, Iran, S. GHADER, Department of Space Physics, Institute of Geophysics, University of Tehran, Iran, M. SHAHSAVARI, Department of Space Physics, Institute of Geophysics, University of Tehran, Iran, A two dimensional fully nonlinear numerical model is presented for simulation of internal gravity waves generated by a buoyancy forcing. The governing equations are written in terms of vorticity and density as prognostic variables, and stream function as a diagnostic variable. A Cartesian geometry with periodic boundary condition in horizontal direction and free-slip boundary conditions at upper and lower boundaries is utilized to perform the computations. A three level leapfrog time stepping method is used to advance the equations in time and the second-order centered finite difference scheme is applied to spatial differencing of the governing equations. Numerical results are presented for non-hydrostatic internal gravity waves. Numerical results are compared with some existing experimental observations showing that the flow structure in formation of shear layers (5-7 layers) is similar. It also appears that only the outflow due to either density point sources (numerical) or plumes (experimental) is important in formation of the internal waves that forms the layers.

M-1E-4. NONLINEAR BI-CHROMATIC WAVE-GROUP EVOLUTION DESCRIBED BY THE AB-EQUATION

MASHURI, Institut Teknologi Bandung, Indonesia, L. S. LIAM, University of Twente, The Netherlands, ANDONOWATI, Institut Teknologi Bandung, Indonesia, The evolution of finite amplitude water surface waves is known to be dominated by an interplay between nonlinear and dispersive effects. Although this is true for any wave-field, these effects are most clearly visible in wave-groups through the deformation of the envelopes. Nevertheless, only very few special wave-groups are known that have an analytic approximate description; maybe the best known one is the Soliton on Finite Background. Here we will study the down-stream evolution of a Bi-Chromatic wave-group using the recently derived AB equation. Although there seem to be no analytic approximations for this case, there are accurate measurements of experiments in large hydrodynamic wave-tanks. Comparison between the evolution described by the AB equation and the experimental results show promising results both qualitatively and quantitatively.

11:00 ~ 12:20 (Room106)

Multiphase and Particle-Laden Flows (I)

Session Chair : Prof. X. J. Zheng, Lanzhou Univ/China

M-1F-1. REMOVAL OF SEDIMENTS DEPOSITED ON RESERVOIR BEDS UTILIZING SIPHONAGE –SMALL SCALE TEST AND ANALYSIS

M. SADATOMI, A. KAWAHARA, T. TAKATA, Kumamoto University, Japan, In water reservoirs for city water and basins for settling sand and clay in hydraulic power stations, sand and mud etc. deposit on their beds, resulting water capacity reduction and water pollution. In order to remove such sediments efficiently, "A New Sediments Removal System Utilizing Siphonage" has been invented by Prof. M. Sadatomi. In the system, siphonage is utilized in order to minimize power consumption, and the suction port of the siphon can slide down automatically for the effective suction of sediments regardless of remaining sediments. As the first step of its development, a small scale apparatus having a siphon pipe of 20 mm I.D and the maximum level difference of $H = 0.95$ m from reservoir surface to siphon exit was constructed, and experiments have been conducted using the apparatus and 1, 2 and 4 mm O.D. ceramics spherical particles. In the experiment, the present system worked very well, and the data on the discharge rates of solid particles and water, Q_S and Q_L , and the solid particles volume fraction in siphon, α_S were obtained. The results showed that Q_L and Q_S data increased with the level difference, and with increasing of particle size, Q_L increased while Q_S decreased, and thus the ratio of Q_S/Q_L decreased. α_S data increased with decreasing of the particle size. In addition to the experiments, a mathematical model based on a one-dimensional steady state energy conservation equation has been proposed to predict the performance of the present system in order to find an optimum design method of the system in practical uses. The calculated results by the model agree well with the data for 2 and 4 mm particles in $H > 0.6$ m. For 1 mm particles, however, the agreement is not enough probably due to the periodical particles stoppages.

M-1F-2. MULTIGRID FICTITIOUS BOUNDARY AND FINITE ELEMENT METHOD FOR LIQUID-SOLID TWO PHASE FLOWS

D. C. WAN, State Key Laboratory of Ocean Engineering, School of Naval

Architecture, Ocean and Civil Engineering, Shanghai Jiao Tong University, China, Direct numerical simulation of solid-liquid two phase flows with large number of moving particles is a very challenging task. The rigid particles are moved by Newton's laws under the action of hydrodynamic forces computed from the numerical solution of the incompressible viscous fluid equations. On the other hand, the fluid fields and domain are disturbed and changed simultaneously due to the motion of the particles. It is crucial that in the practical cases in which many moving particles often exist in fluids, the complex interaction between fluid and particles as well as the collision between particles put a great confrontation to any numerical schemes adopted. In this paper, an explicit multigrid fictitious boundary method (MFBM) coupled with finite element method to simulate the liquid-solid two phase flows with large number of moving particles is presented. The MFBM is based on a multigrid FEM background mesh and starts with a coarse mesh which may contain already many of the geometrical fine-scale details, and employs a (rough) boundary parameterization which sufficiently describes all large-scale structures with regard to the boundary conditions. Then, all fine-scale features are treated as interior objects such that the corresponding components in all matrices and vectors are unknown degrees of freedom which are implicitly incorporated into all iterative solution steps. The main advantage of the MFBM is that the solid particles, which are allowed to have different shape and size, can move freely through the computational mesh for the fluid part which has not to change in time. This MFBM approach can be easily incorporated into almost all CFD codes without the need for additional background meshes for the particles or special interpolation procedures since it only requires changes in the treatment of Dirichlet boundary conditions. Further, in the MFBM, very different shapes and sizes of particles can be easily included; even coalescence and breakup mechanism are possible. Finally, since the presented method is based on simple extensions of standard Navier-Stokes solvers, the 3D case can also be quite straightforward to be fulfilled. In this paper, as an illustration, two numerical simulations of three big disks plunging into 2000 small particles of three different densities and sedimentation of 5,000 particles in a cavity by the MFBM-FEM are presented. The numerical examples show that the presented method provides a robust and efficient approach to simulate solid-liquid two phase flows with large number of moving particles.

M-1F-3. EFFECTS OF A MAGNETIC FIELD ON HEAT TRANSFER COEFFICIENT IN A HEAT EXCHANGER USING MAGNETIC FLUID

H. TSUBONE, Ariake National College of Technology, Japan, Y. NISHIMARU, Mitsubishi Heavy Industries Ltd. Hiroshima Machinery Works, Japan, Y. KOGA, Ariake National College of Technology, Japan, In recent years, magnetic fluid has been developed for a variety of new applications. However, there are not many practical applications for utilizing magnetic fluid. For the purposes of practical applications of magnetic fluid, the authors have proposed a new type of heat exchanger using magnetic fluid, which is capable of controlling heat transfer by means of a magnetic field. Although a lot of study on heat transfer of magnetic fluid have been conducted by many researchers, the effect of location and strength of magnetic fields on heat transfer coefficients in vertical circular pipe are not clarified yet at present. The purpose of this study is to clarify the phenomenon experimentally based on the above mechanism. In this experiment, a water-based magnetic fluid was used as a working fluid under atmospheric pressure. The test pipe in the test section was circular with a 10.2 mm i.d. and 200 mm in length, made of brass. Different sets of permanent magnets were placed at the test section. Experimental data on temperature, heat transfer coefficient etc. were measured under steady state at different experimental conditions of heat flux ($q=1.5 \times 10^4 - 3.4 \times 10^4$ W/m²), liquid volumetric flux ($jL=0.2-0.4$ m/s), positions of the magnetic field for the test section ($z=0$ mm and 45 mm) and strengths of magnetic fields between the magnets at a center axis ($H=0.0093 - 0.0277$ MA/m). Then, experimental result on temperature, heat transfer coefficient etc. were analyzed for various parameters. Especially, effects of position and strength of the magnetic field on heat transfer coefficient in heat exchanger using magnetic fluid were demonstrated. As a result, from the present data, it was confirmed that heat transfer using a magnetic fluid in a heat exchanger can be controlled by location and strength of the magnetic field. In addition, the relationships between Nusselt number and Reynolds number were discussed and some experimental correlations on Nusselt number are proposed in this paper.

M-1F-4. A STUDY OF SEPARATION AND REATTACHMENT PROCESS IN GAS-LIQUID TWO PHASE FLOW

A. IJIMA, Tokyo University of Science, Japan, T. TANABE, Japan, M. MOTOSUKE, Tokyo University of Science, Japan, S. HONAMI, Tokyo