

TM-P043

Ohmic Contact Properties of Nonpolar GaN Grown on r-plane Sapphire Substrate with Different Miscut Angle

Dongsu Shin¹, Jinsub Park^{1,2,*}

¹Department of Electronics and Computer Engineering, Hanyang University, Seoul 133-791,

²Department of Electronic Engineering, Hanyang University, Seoul 133-791, Republic of Korea

The properties of Ni/Au Ohmic contacts formed on nonpolar a-plane GaN grown on r-plane sapphire substrate with different tilt angles are investigated using current-voltage (I-V) measurements. To investigate the effects of pattern direction and size on Ohmic contact properties of a-plane GaN, transmission line method (TLM) patterns are formed either along c-axis and m-axis on nonpolar GaN surface with different size. I-V measurement results show that the size of TLM pattern and formation direction of electrode have an effect on the electrical properties of a-plane GaN. The large sized patterns show the relatively lower sheet resistance compared to the small sized patterns. In addition, the sheet resistance of a-plane GaN along m-axis shows lower values than that along the c-axis. Finally, the effects of miscut angle of r-sapphire substrate (0.2°, 0.4° and 0.6°) on electrical properties of a-plane GaN will be discussed.

Keywords: nonpolar, miscut angle, GaN, Ohmic

TM-P044

Application of Polystyrene/SiO₂ Core-shell Nanospheres to Improve the Light Extraction of GaN LEDs

Seung Hwan Yeon¹, Kiyong Kim¹, and Jinsub Park^{1,2}

¹Department of Electronics and Computer Engineering, Hanyang University,

²Department of Electronic Engineering, Hanyang University, Seoul, Korea

To improve the optical and electrical properties of commercialized GaN-based light-emitting diodes (LEDs), many methods are suggested. In recent years, great efforts have been made to improve the internal quantum efficiency and light extraction efficiency (LEE) and promising approaches are suggested using a patterned sapphire substrate (PSS), V-pit embedded LED structures, and silica nanostructures. In this study, we report on the enhancement of photoluminescence (PL) intensity in GaN-based LED structures by using the combination of SiO₂ (silica) nanospheres and polystyrene/SiO₂ core-shell nanospheres. The SiO₂ nanospheres-coated LED structure shows the slightly increased PL intensity. Moreover the polystyrene/SiO₂ core-shell nanospheres-coated structure shows the more increase of PL intensity comparing to that of only SiO₂ spheres-coated structure and the conventional structure without coating of nanospheres. The Finite-difference time-domain (FDTD) simulation results show corresponding result with experimentally observed results. The mechanism of enhancement of PL intensity using the coating of polystyrene/SiO₂ core-shell nanospheres on LED surface can be explained by the improvement in extraction efficiency by both increasing the probability of light escape by reducing Fresnel reflection and by multiple scattering within the core-shell nanospheres.

Keywords: GaN LED, Silica, Nano, Extraction