government, the solar and space weather group of Korea Astronomy and Space Science Institute has been researching (KASI) towards the prevention of hazardous effects on Korean satellites. the stability of wireless telecommunications, and the safety of polar route aviation. So far, we have expanded the ground observation system, made space data accessible, developed more advanced models for space weather forecasting, from which we have been providing forecasting services to a satisfied clientele. Alongside that, continued our research on solar activities and the Sun-Earth connection. In this talk. summarize our contributions to space weather over the past 10 years and discuss future plans for next decade.

[구 SS-14] 우주환경 예보를 위한 VAP 데이터 처리 시스템 및 실시간 데이터 표출

JongKil Lee¹ Jaejin Lee² KyungChan Kim²

¹ University of Science&Technology,

² Korea Astronomy&Space Science Institute

근지구 우주환경 예측을 위해서는 태양의 주기, 흑점, 그리고 코로나의 방출과 함께 Van Allen Belt에 붙잡힌 고에너지 입자의 상태 변화가 우주 환경의 예보를 위한 중요 요소가 된다. 이런 고에너지 입자를 측정하기 위해서는 Van Allen Belt를 통과하는 VAP 위성의 데이터를 살펴보는 것이 매우 중요하다. 이 연구에서는 한국천문연구원에서 APL과 공동으로 VAP 위성의 실시간 데이터를 송수신하는 시스템을 구축하고, 그 실시간 데이터를 우주환경감시실에서 표출하여 Van Allen Belt의 변화를 바로 알아보는 과정을 기술 하였다. 이를 통해 데이터의 경향성을 바로 과악하여 특정 이벤트의 발생을 알아 낼 수 있을 뿐만아니라 과거의 데이터를 손쉽게 찾아볼 수 있었다. 별도의 프로그램을 개발하여 데이터의 표출 비교를 가능하게 함으로써 다른 위성의 데이터나 태양 이미지를 보지 않아도자체 비교를 통해 이벤트의 발생을 찾아 볼 수 있게 되었다.

[구 SS-15] Development of three-dimensional global MHD model for an interplanetary coronal mass ejection

Jun-Mo An¹, Tetsuya Magara¹, Satoshi Inoue², Keiji Hayashi³, Takashi Tanaka⁴
¹ School of Space Research Kyung Hee University,

²Nagoya University, ³National Astronomical Observatory of China, ⁴Kyushu University

We developed a three-dimensional magnetohydrodynamic (MHD) code to reproduce the structure of a solar wind, the properties of a

coronal mass ejection (CME) and the interaction between them. This MHD code is based on the finite volume method incorporating total variation diminishing (TVD) scheme with an unstructured grid system. In particular, this grid system can avoid the singularity at the north and south poles and relax tight CFL conditions around the poles, both of which would arise in a spherical coordinate system (Tanaka 1994). In this model, we first apply an MHD tomographic method (Hayashi et al. 2003) to interplanetary scintillation (IPS) observational data and derive a solar wind from the physical values obtained at 50 solar radii away from the Sun. By comparing the properties of this solar wind to observational data obtained near the Earth orbit, we confirmed that our model captures the velocity, temperature and density profiles of a solar wind near the Earth orbit. We then insert a spheromak-type CME (Kataoka et al. 2009) into the solar wind to reproduce an actual CME event. This has been done by introducing a time-dependent boundary condition to the inner boundary of our simulation domain. On the basis of a comparison between a simulated CME and observations near the Earth, we discuss the physics involved in an ICME interacting with a solar wind.

[→ SS-16] Full ice-cream cone model for halo coronal mass ejections

Hyeonock Na, Yong-Jae Moon School of Space Research, Kyung Hee University, Yongin, Korea

The determination of three dimensional parameters (e.g., radial speed, angular width, source location) of Coronal Mass Ejections (CMEs) is very important for space weather forecast. To estimate these parameters, several cone models based on a flat cone or a shallow ice-cream cone with spherical front have been suggested. In this study, we investigate which cone model is proper for halo CME morphology using 33 CMEs which are identified as halo CMEs by one spacecraft (SOHO or STEREO-A or B) and as limb CMEs by the other ones. From geometrical parameters of these CMEs such as their front curvature, we find that near full ice-cream cone CMEs (28 events) are dominant over shallow ice-cream cone CMEs (5 events). So we develop a new full ice-cream cone model by assuming that a full ice-cream cone consists of many flat cones with different heights and angular widths. This model is carried out by the following steps: (1) construct a cone for given height and angular width, (2) project the cone onto the sky plane, (3) select points comprising the outer