

(2 line spacing)

## **Instructions for the Preparation of Article for Transactions on Electrical and Electronic Materials (bold, 15 points)**

(1 line spacing)

Gil-Dong Hong\*, Gap-Soon Lee, and Nor-Ree Han

*Department of Electrical and Electronic Engineering, College of Engineering, Yonsei University,  
134 Shinchon-dong, Seodaemoon-ku, Seoul 120-749, Korea*

(1 line spacing)

P. de Smith and Helew Pack

*Department of Electrical Engineering, Old Dominion University,  
Norfolk, VA 23529, U.S.A.*

(1 line spacing)

E-mail : gdhong@ocbc.ac.kr

(1 line spacing)

(Received 2 January 2002, Accepted 15 February 2002)

(1 line spacing)

These pages provide you with an example of the layout and style which we wish you to adopt during the preparation of your paper. Make the width of abstract to be 14cm.

(1 line spacing)

*Keywords* : List less than 5 keywords related to this article

(2 line spacing)

### **1. FORMAT**

(1 line spacing)

We recommend to use MS Word processor and prepare text within the dimensions shown on these pages; In A4 paper, left and right margin are 16mm respectively, 8mm middle margin, 35mm top margin, and 7mm bottom margin. When a paragraph starts, give an indent of 2 characters. In the last page of the article, make the length of left and right stage to be equal approximately.

Make use of the maximum stipulated length apart from the following two exceptions (i) do not begin a new section directly at the bottom of a page, but transfer the reading to the top of the next column; (ii) you may exceed the length of the text area by one line only in order to complete a section of text or a paragraph.

(1 line spacing)

#### **1.1 Spacing**

We normally recommend the use of 1.0 (single) line spacing. However, when typing complicated mathematical text it is important to increase the space between text lines in order to prevent sub- and super-script fonts overlapping one another and making your printed matter illegible.

(1 line spacing)

#### **1.2 Fonts**

These instructions have been produced using a 10.5 point Times Roman font. Title and subtitle are written in bold-faced characters.

(2 line spacing)

### **2. PRINTOUT**

(1 line spacing)

Please make use of good quality plain white A4 paper size. Here we demonstrate a problem which we often experience with computer printout. Printers sometimes produce text which contains light and dark streaks, or considerable lighting variation either between left- and right-hand margins or between text heads and bottoms. To achieve optimal reproduction quality, the contrast of text lettering must be uniform, sharp, and dark over the whole page and throughout the article.

If corrections are made to the printout, run completely new replacement pages. The contrast of these pages should be consistent with the rest of the paper as should text dimensions and font sizes.

(2 line spacing)

### **3. TABLES AND ILLUSTRATIONS**

(1 line spacing)

Tables and illustrations should be originals or sharp prints. They should be arranged throughout the text, preferably being included on the same page as they are first discussed. They should have a self-contained caption and be positioned in center margin within a single column. If they do not fit into one column they may be placed across both columns in which case place them at the top or at the bottom of a page.


(1 line spacing)

(1 line spacing)

### 3.1 Tables

Tables should be presented in the form shown in Table 1. Their layout should be consistent throughout. Horizontal lines should be placed above and below table headings, above the subheadings and at the end of the table. Do not use any notes. Vertical lines should be avoided. If a table is too long to fit onto one page, the table number and headings should be repeated on the next page before the table is continued.


(1 line spacing)



(1 line spacing)

Fig. 1. Good quality figure with clear lettering.

(1 line spacing)



(1 line spacing)

Fig. 2. Bad quality, distorted figure; lettering is too small.

(1 line spacing)

### 3.2 Line drawing

Line drawings should be drawn in India ink on tracing paper with the aid of a stencil or be glossy of the same, if they have not been prepared on your computer facility. They should be attached to your manuscript page, correctly aligned. All illustrations should be clearly displayed by leaving at least a single line of spacing above and below them. When placing a figure at the top of a page, the top of the figure should be at the same level as the bottom of the first text line of the other column.

All notations and lettering should be no less than 2 mm high. The use of heavy black, bold lettering should be avoided as this will look unpleasantly dark when printed.

(1 line spacing)

### 3.3 Black and white photographs

Photographs must always be sharp originals (*not screened versions*) and rich in contrast. They should be pasted on your page in the same way as line drawings.

(1 line spacing)

### 3.4 Color photographs

Sharp originals should be submitted close to the size expected in publication. Charges for the processing and printing of color will be passed on to the author(s) of the paper. As the costs involved are per page, care should be taken in the selection of size and shape so that two or more illustrations may be fitted together on one page.

(2 line spacing)

## 4. EQUATION

(1 line spacing)

Equations are placed in center and should be preceded and followed by one line of white.

(1 line spacing)

$$H\alpha \beta (\omega) = E\alpha (0)\delta \alpha \beta + \langle \alpha : W\pi : \beta \rangle \quad (1)$$

(1 line spacing)

If they are numbered, make sure that they are numbered consecutively. Place the numbers in parentheses. Flush with the right-hand margin of the column and level with the last line of the equation.

(2 line spacing)

## ACKNOWLEDGMENTS

(1 line spacing)

This work was supported by the Ministry of Science and Technology through the Nano-Structure Technology Project.

(2 line spacing)

## REFERENCES

(1 line spacing)

- [1] D. A. Neamen, "Semiconductor Physics and Device", Irwin, p. 10, 1997.
- [2] T. W. Choi, "Electrical and mechanical properties of ceramics", Bulletin of KIEEME, Vol. 15, No. 1, p. 1.

)

- 2001.
- ] T.-W. Choi and S.-C. Yoo, "Electrical and mechanical properties of ceramics", J. of KIEEME(in Korean), Vol. 15, No. 1, p. 10, 2001.
  - ] T. W. Choi, C. S. Lee, and S. C. Yoo, "Electrical and mechanical properties of ceramics", Trans. on EEM, Vol. 15, No. 1, p. 10, 2001.
  - ] Tae Wuk Choi and Sang Chul Yoo, "Electrical and mechanical properties of ceramics", J. Mater. Sci., Vol. 15, No. 1, p. 10, 2001.
  - [6] T. W. Choi, "Electrical properties of ceramics", Ko Report, No. KR-R250, p. 10, 2001.
  - [7] T. W. Choi and S. C. Yoo, "Electrical ceramics", SID digest paper, p. 10, 1995.
  - [8] T. W. Choi and S. C. Yoo, "Electrical ceramics", Pt 2002 Summer Conf. KIEEME, p. 10, 2002.
  - [9] T. W. Choi, "Electrical properties of ceramics", Patent, 1,234,567, 2001.

## Contributions

**Manuscripts** for publication should be sent in triplicate (along with the electric form) to the Korean Institute of Electrical and Electronic Material Engineers. Manuscripts from countries outside Korea may be submitted through the appropriate international editors depending on the subject area, or directly to the Korean Institute of Electrical and Electronic Material Engineers.

A **Submitted Manuscript** is accepted with the understanding that the manuscript is not currently under consideration by another journal and that it has not been copyrighted or accepted for publication elsewhere.

**General Style.** Manuscripts must be prepared in accordance with the general requirements that are summarized in Instruction for Authors for Publication published in the back of the first issue of every volume.

**Iteration in Proof.** A limited number of alterations in proof are allowed, but the cost of making extensive corrections and changes after an article has been set in type will be charged to the author. Proofs and all correspondence concerning papers in the process of publication should be returned to the same address as that to which the initial manuscript was sent.

**Subscriptions, renewals, and changes of address** should be addressed to the Office of the Korean Institute of Electrical and Electronic Material Engineers. For a change of address, please send both old and new addresses.