

testo 105

testo 105

- 3가
- 가 가
- High/Low
- 2
- IP 65
-
-



02)2672-7200 / FAX : 2679-9853

2-21 1

<http://www.testo.co.kr/>



| | |
|-------------------|--|
| 기술데이터 | testo 105 |
| 패러미터 | °C / °F |
| 센서 | NTC |
| 측정 채널 | 1 채널 |
| 측정 범위 | -50... +275 °C |
| 분해능 | 0.1°C |
| 정확도 | ±0.5 °C(-20 ~ 100 °C) ±1 %(100.1 ...275 °C) 1 °C (-50... -20.1 °C) |
| 디스플레이 | LCD, 1라인 |
| 센서 | NTC 헤드 (플러그인 타입) |
| 스탠다드(t99 < 15초) | length 120 mm |
| 냉동 식품용(t99 < 60초) | length 90 mm |
| Long (t99 < 15초) | length 200 mm |
| 측정주기 | 2 measurements per second |
| 작동온도 | -20... +50°C |
| 보관온도 | -40... +70°C |
| бат데리 타입 | 4x리튬 бат데리(LR44) |
| бат데리 수명 | 80시간(자동 on/off 10분) |
| 하우징(외관) | ABS(손잡이부분은 소프트코팅), IP65 |
| 크기 | 145x38x195mm |
| 무게 | 139 g |
| 보증 | 본체 2년, 프로브 1년 |

